



ALUMINUM BODY MAXIMUM O.A.L. 384.00" FRONTAL IMPACT PROTECTION SIDE ROLL PROTECTION

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- ONEPOT AUTOMATIC TIRE CHAINS TO BE PROVIDED AT REAR
- MOUNTING BRACES FOR ANTENNA LOCATED PER SHOP ORDER
- KUSUMAL PUMP PLUS 1000 BATTERY CHARGER/AIR COMPRESSOR LOCATED IN CREW CAB SEAT REAR
- PERIMETER SCENE LIGHTS LOCATED PER SHOP ORDER
- L-SHAPED DRIP PAN BARS FOR ALL ROLL-UP DOORS
- RIVETS L.E.D. COMPARTMENT DUAL LIGHT STRIPS LOCATED PER SHOP ORDER
- CIRCUIT BREAKER PANEL IN COMPARTMENT D3
- STAINLESS STEEL FENDER CURBS FRONT AND REAR
- PIERCE LOAD REEL LAPS FRONT AND REAR PUMP PANEL
- AIR INLET WITH DISCONNECT FITTING LOCATED ON D.S. PUMP PANEL

- PAINTED SHELF TRACKS IN COMPARTMENTS D1, D3, P1, P2 & R1
- HANWAY ELECTRIC REWIND CABLE REEL 160-152-18 (B.O.M.) WITH 200' OF 10/3 CABLE, REEL UNITION BOX AND HOLDER
- ONE 40-GAL. FLOOR MOUNTED TRAY IN COMPARTMENTS D1, D3 AND R1
- ALUMINUM 4-WAY ON FLOOR OF COMPARTMENT P1
- ONE PAINTED ADJUSTABLE FILL WITH OPTICOM SHELF IN COMPARTMENT D2
- ALUMINUM PROGUARD WITH TRACK ON REAR WALL OF COMPARTMENT D1 & D3
- 1.00" RETAINING LIP ON TOP OF EXTINGUISHER BIN IN COMPARTMENT P2
- ALUMINUM PROGUARD WITH TRACK ON REAR WALL OF COMPARTMENT D2
- STORAGE BIN FOR (3) EXTINGUISHERS ON FLOOR OF COMPARTMENT P2
- TWO 15A, 120V DUPLEX RECEPTACLES LOCATED IN CAB

CUSTOMER APPROVAL			
APPROVED BY:	CHASSIS DATA	TITLE	1500-D-675P W/40 GAL FOAM CELL, 161" FH D5, LOW PS (2) XLYS, GENERATOR, BOOSTER REEL, HUSKY 3
DATE:	TIME	FOR	HATFIELD VOLUNTEER FIRE COMPANY #1 HATFIELD, PENNSYLVANIA
	PIERCE	DWG NO.	26476AD
REV	DATE	BY	CH
1			
2			
3			
4			
5			

Plato MANUFACTURING INC.		JOB NO.	26476
SCALE	1:24	DATE	
DRAWN BY	NPA	OSNOV12	
CHECKED BY	CSH	06NOV12	
SHEET SIZE	D	SHEET NO.	1 of 1