



ALUMINUM BODY MAXIMUM O.A.H. = 137.00" (11'-5.00") MAXIMUM O.A.L. = 492.00" (41'-0") SIDE ROLL AND FRONTAL IMPACT PROTECTION

- NOTE: DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.
- ONE (1) AUTOMATIC FIRE CHAINS TO BE PROVIDED AT REAR
 - AIR LINE WITH DISCONNECT COVER TO BE ON THE DRIVER SIDE STEP WELL
 - ONE (1) 12V BATTERY COMPARTMENT TO BE PROVIDED IN COMPARTMENT D1
 - MOUNTING BASE FOR ANTENNAS LOCATED PER SHOP ORDER
 - BATTERY CHARGER MOUNTED BEHIND PASSENGER'S SIDE SEAT
 - BATTERY CHARGE INDICATOR LOCATED ON D.S. SEAT RISER
 - SEVENTEER SOLAR LIGHTS LOCATED PER SHOP ORDER
 - SHIP PAN GUARD FOR ROLL-UP DOOR IN COMPARTMENT D1, D2, D3, D4, D6, P1, P2, P3, P4, P6
 - ON WHELEN L.E.D. COMPARTMENT LIGHTS IN COMPARTMENT D1, D2, D3, D4, D6, P1, P2, P3, P4, P6
 - SHIELD TRACKS IN COMPARTMENT D1, D3, D4, D6, P1, P3, P6 & FORWARD OF VERTICAL DIVIDER IN P4
 - ONE (1) FULL WIDTH/DEPTH PAINTED ADJUSTABLE GATE IN COMPARTMENT D1, P1 & ONE (1) IN D4, P4
 - ONE (1) FLOOR MOUNTED SLIDE-OUT TRAY (FULL DEPTH/FULL WIDTH) IN COMPARTMENT D1, D4, P1
 - ONE (1) FLOOR MOUNTED 2-WAY SLIDE-OUT TRAY IN COMPARTMENT D6-P6
 - ONE (1) ADJUSTABLE TILTING SLIDE-OUT TRAY IN COMPARTMENT D3
 - ONE (1) SLIDE-OUT TOOL BIN/BOXES IN COMPARTMENT D3
 - ONE (1) SHOWER FOR EXTENSIVE WASHING W/HELEN IN COMPARTMENT D1
 - ONE (1) ALUMINUM VERTICAL DIVIDER IN COMPARTMENT P1, P4
 - FLOOR EXTENSION IN COMPARTMENT D6, P6
 - FOUR (4) PIKE POLE STORAGE TUBES IN COMPARTMENT D6-P6
 - CIRCUIT BREAKER PANEL IN COMPARTMENT D5
 - SUB FEED BREAKER BOX IN COMPARTMENT D5
 - ONE (1) HARMON ELECTRIC HEATING CORD REEL MODEL 1618-17-18 LOCATED HIGH AND FORWARD IN COMPARTMENT D4 L & R EACH WITH 200' OF 10-3 GA. CABLE, CIRCLE-O JUNCTION BOX AND 5/8" SLIDER
 - ONE (1) 24V 120L RECEPTACLE IN COMPARTMENT P3
 - TWO (2) 15A 120V DUPLEX RECEPTACLE LOCATED IN CAB
 - INSTALL CUSTOMER SUPPLIED OPS ANTENNA PER SHOP ORDER
 - STANDARD FOLDING STEPS MOUNTED ON THE AERIAL DEVICE PER SHOP ORDER
 - STABILIZER MOUNTED FOR 18.00" BUMP PENETRATION
 - STAINLESS STEEL SHIRTMENTER ON AERIAL LADDER SECTIONS
 - 120V POWER TO AERIAL TIP
 - 2-WAY INTERCOM SYSTEM BETWEEN AERIAL TIP AND TURNTABLE
 - LIFTING EYE RESCUE ATTACHMENT AT AERIAL TIP
 - COLLECTION HOISTING CONTROL SYSTEM ON AERIAL DEVICE
 - 2.00" RAISED PEDestal
 - TWO (2) PAIR OF 21" MATIC SAC-44-E FOLDING WHEEL CHOCKS SHIPPED LOOSE

CUSTOMER APPROVAL				JOB NO. 26399	
APPROVED BY:	DATE:	CHASSIS DATA	TITLE	SCALE	DATE
			105 AERIAL LADDER & BODY ASSEMBLY (105HDL) NO TANK / NO PUMP	1:24	
			FOR PLYMOUTH FIRE COMPANY CONSHOHOCKEN, PA		
			DWG NO. 26399AD		
REV	DATE	BY	CHK	AXT8110	