



ALUMINUM BODY    MAXIMUM O.A.H. 138.00"

- NOTE**  
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.
- ONSPOT AUTOMATIC TIRE CHAINS TO BE PROVIDED AT REAR
  - AIR INLET WITH DISCONNECT FITTING LOCATED IN DRIVER SIDE STEP WELL
  - MOUNTING BASE FOR ANTENNA LOCATED PER SHOP ORDER
  - BATTERY CHARGER LOCATED BEHIND DRIVER SEAT
  - BATTERY CHARGER INDICATOR LOCATED ON DRIVER SIDE SEAT REAR
  - SUB-FEED CIRCUIT BREAKER PANEL IN COMPARTMENT-D5
  - PERIMETER SCENE LIGHTS LOCATED PER SHOP ORDER
  - STAINLESS STEEL GUARD/DRIP PAN ON COMPARTMENT-D1,D2,D3,D4,P1,P2,P3,P4
  - PIERCE L.E.D. LIGHT STRIPS LOCATED IN ALL SPECIFIED BODY COMPARTMENTS
  - SHELF TRACKS LOCATED IN ALL SPECIFIED BODY COMPARTMENTS
  - CIRCUIT BREAKER PANEL LOCATED IN COMPARTMENT-D5
  - ONE 120V DUPLEX RECEPTACLE ON EACH SIDE OF ENGINE TUNNEL
  - EBERHARD FOLDING STEPS MOUNTED ON AERIAL DEVICE PER SHOP ORDER
  - MOUNTING BRACKETS AT THE AERIAL FLY SECTION FOR (CTF) 8" FIRE HOOKS PIKE POLE
  - MOUNTING BRACKETS AT THE AERIAL FLY SECTION FOR (1) AXE
  - 21.00" AERIAL LIMITED RETRACTION
  - MOUNTING BRACKETS FOR 14" DUO-SAFETY 575-C ROOF LADDER AT THE BASE SECTION
  - 2.00" LOWERED TURNABLE
  - 120V POWER TO AERIAL TIP
  - FIRE RESEARCH 2-WAY RADIO INTERCOM SYSTEM MOUNTED PER SHOP ORDER
  - AERIAL PEDESTAL RAISED 3.00"
  - LIFTING EYE RESCUE ATTACHMENT AT AERIAL TIP
  - ONE 120V DUPLEX RECEPTACLE IN COMPARTMENT-D4,P4
  - STABILIZERS MODIFIED FOR 18.00" GROUND PENETRATION

REV	DATE	BY	CH	ARROWXT
23JAN15	STU	DTS		CHASSIS DATA
13NOV14	BST	DTS		MAKE
16OCT14	BST	DTS		PIERCE
22AUG14	BST	JBL		MODEL

		JOB NO.	28174
		SCALE	DATE
TITLE	105' HSL AERIAL LADDER AND BODY ASSEMBLY	DRAWN BY	BST
FOR	500 GALLON WATER TANK	CHECKED BY	JBL
	LOWER FREDERICK FIRE COMPANY	SHEET SIZE	SHEET NO.
	SPRING MOUNT, PA	DWG NO.	28174AD
			1 OF 1