



ALUMINUM BODY

MAXIMUM O.A.H. 118.00"

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 5/STL SCUFFPLATE ON EACH CAB DOOR JAMB
- BATTERY CHARGER/AIR COMPRESSOR LOCATED BEHIND DRIVER'S SEAT
- PERIMETER SCENE LIGHTS LOCATED PER SHOP ORDER
- 5/STL PROTECTIVE GUARD FOR ROLL-UP DOOR IN COMPARTMENTS D1,D2,D3,P1,P2,P3,R1
- PIERCE L.E.D. DUAL COMPARTMENT LIGHT STRIPS LOCATED PER SHOP ORDER
- PAINTED SHELF TRACKS LOCATED IN COMPARTMENTS D1,D2,D3,P1,P2,P3
- ONE FULL WIDTH/DEPTH PAINTED ADJUSTABLE SHELF IN COMPARTMENTS D1,D2,D3,P1,P2,P3
- ONE FLOOR MOUNTED SLIDE-OUT TRAY WITH SIDES IN COMPARTMENT R1
- PARTITION BETWEEN COMPARTMENTS D1/R1 AND P1/R1
- ALL FOLDING STEPS TO BE TRIDENT WITH INTEGRATED L.E.D. LIGHT UNLESS SPECIFIED
- AIR INLET WITH DISCONNECT COUPLING IN O.S. STEP WELL
- ONE 120V DUPLEX RECEPTACLE LOCATED IN CAB

REV	DATE	BY	CH	SABER FR
26	JAN 15	JAF	-	PIERCE
11	DEC 14	JCH	CAG	PIERCE

		JOB NO.	28400
		SCALE	DATE
TITLE	1250D-975P W256 FOAM, 161" FULL HEIGHT, FDLER (3) X-LAYS, DELUGE		
FOR	GLICK FIRE EQUIPMENT CO, INC BIRD IN HAND, PENNSYLVANIA		
DWG NO.	28400AD		
DRAWN BY	JWO	CHECKED BY	CSH
SHEET SIZE	D	SHEET NO.	1 OF 1