



- HOSEBED CAPACITIES**
- ① 200' OF 2.50" D.J. POLY HOSE
 - ② 300' OF 2.00" D.J. POLY HOSE
 - ③ 200' OF 1.75" D.J. POLY HOSE
 - ④ 1200' OF 5.00" D.J. POLY HOSE
 - ⑤ 400' OF 3.00" D.J. POLY HOSE
 - ⑥ 400' OF 3.00" D.J. POLY HOSE

ALUMINUM BODY
 MAXIMUM O.A.L. 379.00" MAXIMUM O.A.H. 123.00" SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 1. BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT
- 2. BATTERY CHARGE INDICATOR LOCATED ON DRIVER'S SEAT RISER
- 3. DUAL L.E.D. LIGHT STRIPS LOCATED IN HOSE BED
- 4. DRIP PAN GUARD FOR ROLL-UP DOOR LOCATED R1
- 5. CIRCUIT BREAKER PANEL IN COMPARTMENT D3
- 6. PAINTED SHELF TRACKS LOCATED IN COMPARTMENTS D1, D2, D3, P1, P3, R1

REV	DATE	BY	CH	ENFORCER
13MAR18	CUP	DTS	MAKE	
15FEB18	CUP	DTS	PIERCE	
10JAN18	CUP	CDU	MODEL	

		JOB NO.	32038
		SCALE	DATE
TITLE	1500-D-520P, 500 GAL WATER W/20 GAL FOAM, 161" BODY (4) XLAYS, DELUGE, GENERATOR, CABLE REEL	DRAWN BY	CUP
FOR	STEELTON FIRE DEPARTMENT STEELTON, PENNSYLVANIA	CHECKED BY	CDU
DWG NO.	32038AD	SHEET SIZE	SHEET NO.
		D	1 OF 1