



(SIDE ROLL AND FRONTAL IMPACT PROTECTION)

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

NOTES: 1. AIR INLET WITH A DISCONNECT COUPLING IS LOCATED IN THE DS STEP WELL - REARWARD.

MAXIMUM O.A.H.: 11' - 8.0"
MAXIMUM O.A.L.: 38' - 0.0"

CLEAR DOOR WIDTH KEY

ANDOR ROLL UP DOORS:	-2 1/4"
GORITTE ROLL UP DOORS:	-2 1/2"
PIERCE DOUBLE LAP DOORS:	-4 1/4"
PIERCE LIFT-UP LAP DOORS:	-1 1/2"

(EX: 60" F-F - 2 1/4" = 57 3/4" CLEAR)
(F-F) = FRAME TO FRAME

CUSTOMER APPROVAL

APPROVED BY: _____
DATE: _____

REV	DATE	BY	CH

Pierce MANUFACTURING INC.

TITLE: HEAVY DUTY RESCUE COMBO NONWALK-IN / WALK-IN
FOR: CRANBERRY TOWNSHIP
BID #776

DAN JERIOSKI

DWG NO. 71413-SH1

JOB NO.	PRELIM
SCALE	DATE
1:24	04JAN24
DRAWN BY	CHECKED BY
SHD	-
SHEET SIZE	SHEET NO.
D	1 OF 1