



ALUMINUM BODY

MAXIMUM O.A.L. 362.75"

MAXIMUM O.A.H. 117.00"

SIDE ROLL PROTECTION

**NOTE**  
 1. DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION.  
 MINOR DETAILS NOT SHOWN.

- AIR INLET/OUTLET WITH DISCONNECT FITTING ON DRIVER SIDE PUMP PANEL
- DRIFT AUTOMATIC TIRE CHAINS
- BROUDED S/S/PL SCUFFPLATE ON INTERIOR OF CAB DOORS
- BROUDED S/S/PL SCUFFPLATE SIDES AND REAR OF ENGINE TUNNEL
- S/S/PL SCUFFPLATE ON EACH CAB DOOR JAMB
- HOUSING BASE FOR ANTENNA LOCATED PER SHOP ORDER
- KOSMAMP PUMP PLUS 1200 BATTERY CHARGER LOCATED BEHIND OFFICER SEAT
- BATTERY CHARGE INDICATOR LOCATED ON DRIVER SEAT RISER
- S/S/PL SCUFFPLATE ON REAR OUTER CORNER OF BODY
- REVERSED HINGED DOOR ON COMPARTMENT D3
- S/S/PL SCUFFPLATE ON BOTTOM EDGE OF DOOR FRAMING OF SIDE BODY COMPARTMENTS
- S/S/PL SCUFFPLATE INSIDE EACH BODY COMPARTMENT DOOR
- PAINTED TRIM ON DRIVER SIDE BODY SEAMS
- BOLT-IN PARTITION BETWEEN COMPARTMENTS B1-B1 AND P1-R1
- L.E.D. FRONTIER SCENE LIGHTS LOCATED PER SHOP ORDER
- CIRCUIT BREAKER PANEL IN COMPARTMENT D3
- ONE HANWAY ELECTRIC REWIND CORD REEL MODEL 1618-17-18 LOCATED IN R1 WITH 200' OF 10/3 CABLE AND AKRON JUNCTION BOX

18. ON SCENE SOLUTIONS 54.00" L.E.D. NIGHT STICK AT FRONT OF HOSEBOX

**CUSTOMER APPROVAL**  
 APPROVED BY: \_\_\_\_\_  
 DATE: \_\_\_\_\_

<b>MANUFACTURING INC.</b>		JOB NO.	23788
		SCALE	1:24
<b>1500-D-550P, 500 GAL WATER W/50 GAL FOAM CELL, 140" BODY DS FULL HIGHT &amp; DPTH FRNT &amp; REAR, P5 LOW FLDR</b>		DATE	04AUG10
		DESIGN BY	CSH
<b>FOR PAXTANGS FIRE COMPANY HARRISBURG, PENNSYLVANIA</b>		CHECKED BY	CSH
		DATE	05AUG10
CHASSIS DATA MAKE: PIERCE MODEL: 180C110 SHI DTS REV: 040C110 SHI DTS DATE: _____ BY: CH		TITLE	DWG NO. 23788AD
SHEET SIZE D		SHEET NO.	1 of 1