

PUMPER BODY

Short Aluminum 2nd Gen Pumper

CHASSIS

Saber FR Chassis

CHASSIS

AXLE,FRONT,CUSTOM

19,500 lb TAK-4 Axle

AXLE,REAR

24,000 lb Dana Axle

ENGINE

450 HP Cummins X10 Engine

TRANSMISSION

Allison 6th Gen, 3000 EVS P

BUMPER

19" Extended Painted Steel

CAB

6000 Saber FR Cab

BODY

TOTAL TANK CAPACITY

750 Gallon Poly Tank

WATER CAPACITY

750 Gallons of Water

FOAM CELL

Foam Cell Not Required

COMPT,PUMPER,REAR

30.75" FF-Rear Compt

COMPT,PUMPER,LEFT SIDE

145" Rollup Full Height Front & Rear

COMPT,PUMPER,RIGHT SIDE

145" Rollup Low

FIRE SUPPRESSION

PUMPHOUSE

45" Control Zone Side Mount

PUMP

1500 GPM Waterous CSU

CROSSLAYS,1.50"

1.50" Crosslay Not Required

CROSSLAYS,2.50"

2.50" Crosslay Not Required

SPEEDLAYS

Speedlays Not Required

GENERATOR

Generator Not Required

FOAM SYSTEM

Foam System Not Required

SAFETY

Side Roll and Front Impact Protection

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION.
MINOR DETAILS NOT SHOWN.

1. ONE 2.50 OUTLET WITH 2.50 PIPING AND SWIVEL LOCATED ON TOP OF THE LEFT SIDE OF THE BUMPER

2. SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CAB

3. AIR INLET WITH DISCONNECT COUPLING IN THE DRIVER SIDE STEPWELL

4. BATTERY CHARGER LOCATED PER ORDER

5. BATTERY CHARGE INDICATOR LOCATED ON THE DRIVER SIDE SEAT RISER

COMPARTMENT IPO CROSSLAYS WITH DOOR EACH SIDE

(1) HWIZ FT-B-72-ML VISOR LIGHT

WHELEN FREEDOM IV 72" L.E.D. LIGHTBAR

8.00" CONVEX CROSS VIEW MIRROR

RETRAC HEATED/REMOTE CONTROL MIRRORS WITH CONVEX SECTION

(2) WHELEN M6 L.E.D. WARNING LIGHT IN A COMMON BEZEL EACH SIDE

CENTER HOSE TRAY FOR 150' OF 1.75" HOSE

(1) WHELEN SA315P SPEAKER WITH S/STL GRILLE

(3) WHELEN M6 L.E.D. WARNING LIGHTS EACH SIDE

(2) HADLEY AIR HORNS

(1) FEDERAL Q2B SIREN

120.00 (10'-0") APPROX O.A.H.

4.00

30.75

RS1

RS2

FREE FLOATING RUNNING BOARD HOSE TRAY FOR SET OF 5.00" HOSE

STIRRUP SWITCH FOR HOSE REEL

(1) HANNAY BOOSTER REEL WITH CAPACITY FOR 200' OF 1.00" BOOSTER HOSE AND 1.50" PIPING (MODEL: EF24-28-29)

40.75

66.50

ALUMINUM TREADPLATE WIND DEFLECTOR

61.00

84.00

145.00

30.00

70.00

32.37 CLEAR

35.00

OUTLET, 3.00" DELUGE W/FTT EXTEND-A-GUN XH12 RISER WITH AKRON 3426 MONITOR AND AKRON 2499 QUAD STACKED TIPS WITH 3488 SHAPER AND 4 BOLT FLANGE

(1) WHELEN PSTANK2 L.E.D. WATER LEVEL GAUGE EACH SIDE

(1) HWIZ FT-MB-27-L.E.D. SCENE LIGHT EACH SIDE

(1) TROUGH FOR 6" X 10" HARD SUCTION HOSE (CTF) EACH SIDE

(2) WHELEN MCFED2 L.E.D. WARNING LIGHTS

(4) 2.50" OUTLETS

(2) LIGHTS,REAR SCENE, WLN PEL2*

(2) WHELEN M6 L.E.D. WARNING LIGHTS STOP/TAIL LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN M6 PIERCE BEZELS

(4) 0.25" HOSE BED DIVIDERS

(2) HWIZ FT-MB-2.6-L.E.D. SCENE LIGHTS

(1) PIERCE BACKUP CAMERA (RECESSED)

DUO-SAFETY LADDERS:
(1) 24' 2-SECTION 900A
(1) 14' ROOF 775A
(1) 10' FOLDING 585A
(2) ALUMINUM PIKE POLE TUBES

5'-7"

4.00" INLET W/ 4.00" PLUMBING AND 4.00" X 5.00" STORZ ELBOW

8.00" NFPA MIN.

8.00" NFPA MIN.

17.00

33.50

7.00

5.25

5.25

12.00

72.00

35.00

41.50

46.00

84.00

38.00

4.00

30.75

36.00

27.75

14.00

68.00

14.00

28.00

40.00

28.00

96.00

18.50

64.75

47.50

2.25

27.13 R

2.00

45.00

107.50 CA

59.00

31.50

35.50

57.50 FC

58.00

28.00

16.00

86.00

167.50 WB

357.50 (29'-9.50") APPROX OAL

88.00

60.00

79.25

9.00

17.00

51.50

24.50

1.50

HOSEBED CAPACITIES

- ① 250' OF 2.50" D.J. POLY HOSE
- ② 250' OF 2.50" D.J. POLY HOSE
- ③ 800' OF 3.00" D.J. POLY HOSE
- ④ 1200' OF 4.00" D.J. POLY HOSE
- ⑤ 400' OF 1.75" D.J. POLY HOSE

Pierce MANUFACTURING INC.		PROPOSAL	1078
TITLE		SCALE	DATE
PIERCE		DRAWN BY	15JUL2025
FOR		CHECKED BY	N/A
DWG NO.		SHEET SIZE	SHEET NO.
PRELIMINARY PRINT ONLY		D	1 of 1

CHASSIS DATA	TITLE	PIERCE PUMPER APPROVAL DRAWING
MAKE	FOR	GLICK FIRE EQUIPMENT COMPANY, INC
MODEL	FOR	BIRD-IN-HAND, PA
SABER FR	DWG NO.	PRELIMINARY PRINT ONLY